

11-28-00

A

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

11/27/00
jc871 U.S. PTO

In Re Application of: Broome et al.

Examiner in immediately
preceding parent appln.: Smith, J.

Serial No.: unknown

Anticipated Group Art Unit: 3732

Filed: November 27, 2000

jc658 U.S. PTO
09/723003
11/27/00

For: DISTAL PROTECTION DEVICE AND METHOD

Docket No.: 1001.1350102


TRANSMITTAL SHEET

The Assistant Commissioner for Patents
Washington, D.C. 20231

Sir:

CERTIFICATE UNDER 37 C.F.R. 1.10: The undersigned hereby certifies that this paper or papers, as described herein, are being deposited in the United States Postal Service, "Express Mail Post Office to Addressee" having an Express Mail mailing label number of : EL593905773US , in an envelope addressed to: Assistant Commissioner for Patents, Washington, D.C. 20231 on this 27th day of November , 2000.

By



Lisa A. Dahline

We are transmitting herewith the attached Continuation Patent Application filed under 37 CFR §1.53(b), including the following:

☒ 24 sheet(s) of specification.

☒ 5 sheet(s) of claim(s).

☒ 1 sheet(s) of Abstract.

☒ 20 sheet(s) of formal/informal drawings.

☒ Executed Declaration and Power of Attorney.

☐ A verified statement(s) to establish small entity status under 37 C.F.R. 1.9 and/or 1.27 is enclosed.

☐ An Assignment of the invention to _____ is being filed contemporaneous with this patent application.

☐ A certified copy of a _____ application, serial no. _____, filed _____, 19____, the right of priority of which is claimed under 35 U.S.C. 119.

09723003 11/27/00

CLAIMS AS FILED						
	(1)	(2)	SMALL ENTITY		OTHER	
FOR:	# FILED	# EXTRA	Rate	Fee	Rate	Fee
BASIC FEE				\$355		\$710
TOTAL CLAIMS	-20 =		x9=	\$	x18=	\$
INDEPENDENT CLAIMS	-3 =		x40=	\$	x80=	\$
() MULTIPLE DEPENDENT CLAIM PRESENTED			+135=	\$	+270=	\$
TOTAL			\$		\$	

*If the difference in Column (1) is less than zero, enter "0" in Column 2.

[X] Other Copy of a Revocation of Prior Powers of Attorney and Power of Attorney and twelve (12) sheets of formal drawings.

[X] A check in the amount of \$ 710.00 is enclosed.

[X] Please charge any deficiencies or credit any overpayment in the enclosed fees to Deposit Account No. 50-0413.

By: 

Glenn M. Seager, Reg. No. 36,926

CROMPTON, SEAGER & TUFTE, LLC
 331 Second Avenue South
 Suite 895
 Minneapolis, Minnesota 55401-2246
 Tel: (612) 677-9050
 Fax: (612) 359-9349

DISTAL PROTECTION DEVICE AND METHOD

CROSS-REFERENCE TO RELATED APPLICATION

This application claims priority to copending application Serial No. 08/943,358, filed October 3, 1997, entitled DISTAL PROTECTION DEVICE AND METHOD and assigned to the same assignee as the present invention, and application Serial No. 08/810,825 filed March 6, 1997, entitled DISTAL PROTECTION DEVICE and assigned to the same assignee as the present invention.

BACKGROUND OF THE INVENTION

The present invention deals with an emboli capturing system. More specifically, the present invention deals with an emboli capturing system and method for capturing embolic material in a blood vessel during an atherectomy or thrombectomy procedure.

Blood vessels can become occluded (blocked) or stenotic (narrowed) in a number of ways. For instance, a stenosis may be formed by an atheroma, which is typically a harder, calcified substance which forms on the lumen walls of the blood vessel. A stenosis may also be formed of a thrombus material, which is typically much softer than an atheroma but can nonetheless cause restricted blood flow in the lumen of the blood vessel. Thrombus formation can be particularly problematic in a saphenous vein graft ("SVG").

Two different procedures have been developed to treat a stenotic lesion (stenosis) in vasculature. One is deformation of the stenosis to reduce the restriction within the lumen of the blood vessel. This type of deformation, or dilatation, is typically performed using balloon angioplasty.

Another method of treating stenotic vasculature is to attempt to completely remove the entire stenosis, or enough of the stenosis to relieve the restriction in the blood vessel. Removal of the stenotic lesion has been performed through use of radio frequency ("RF") signals transmitted via conductors, and also through use of lasers. Both of these treatments are intended to ablate (i.e., super heat and vaporize) the stenosis. Removal of the stenosis has also been accomplished using thrombectomy or atherectomy. During thrombectomy and atherectomy, the stenosis is mechanically cut or abraded away from the vessel. However, problems may be encountered during thrombectomy and atherectomy because the stenotic debris which is separated from the stenosis is free to flow within the lumen of the vessel. If the debris flows distally, it can occlude distal vasculature and cause significant problems. If it flows proximally, it can enter the circulatory system and form a clot in the neural vasculature or in the lungs, both of which are highly undesirable.

Prior attempts to deal with the debris or fragments produced during thrombectomy and atherectomy have included cutting the debris into pieces small enough (having a size on the order of a blood cell) that they will not occlude vessels within the vasculature. However, this technique has certain problems. For instance, it is difficult to control the size of the fragments which are severed from the stenotic lesion. Larger fragments may be severed accidentally. Also, since thrombus is much softer than an atheroma, it tends to break up easier when mechanically engaged by a cutting instrument. Therefore, at the moment that the thrombus is mechanically engaged, there is a danger that

it can be dislodged in large fragments which would occlude the vasculature.

Another attempt to deal with debris severed from a stenosis is to remove the debris as it is severed, using suction. However, it may be necessary to pull quite a high vacuum in order to remove all of the pieces severed from the stenosis. If the vacuum used is not high enough, all of the severed pieces will not be removed. Further, use of a high vacuum may tend to cause the vasculature to collapse.

A final technique for dealing with the fragments severed during atherectomy of the stenosis is placement of a device distal to the stenosis during atherectomy to catch the pieces of the stenosis as they are severed, and removal of those pieces along with the capturing device when the atherectomy procedure is complete. Such capture devices have included expandable filters which are placed distal of the stenosis to capture stenosis fragments. Problems are also associated with this technique. For example, delivery of such devices in a low-profile pre-deployment configuration can be difficult. Further, some devices include complex and cumbersome actuation mechanisms. Also, retrieving such capture devices, after they have captured emboli may be difficult.

SUMMARY OF THE INVENTION

The present invention provides a device adapted for deployment in a body vessel for collecting emboli. The device includes a proximally-tapered collapsible frame for operably supporting the filter between a collapsed insertion profile and an expanded deployment profile. The tapered frame includes a mouth which is sized to extend to walls of a body cavity in

the expanded deployed profile for collecting emboli floating in the body cavity.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of an embodiment of a protection device in a radially-expanded deployed profile.

FIG. 2 is a view of the protection device of FIG. 1 in a somewhat collapsed profile.

FIG. 3 is an end view of the protection device of FIG. 1 in a radially-expanded deployed profile.

FIG. 4 is a plan view of a wire mesh sheet for construction of a frame of the protection device illustrated in FIG. 1.

FIG. 5 is a view of the protection device of FIGS. 1-3 in a collapsed profile being inserted through a vessel via an insertion sheath.

FIG. 6 is a view of the protection device of FIGS. 1-3 inserted into a vessel via the insertion sheath, where the insertion sheath is withdrawn to deploy the protection device for operation.

FIG. 7 is a view of the protection device of FIGS. 1-3 operating in a vessel in an expanded deployed profile and illustrating a retrieval sheath for withdrawal of the deployed protection device.

FIG. 8 is a perspective view of an alternate embodiment of a protection device shown in a radially-expanded deployed profile.

FIG. 9 is a view of the protection device of FIG. 8 in a collapsed profile, inserted into a vessel via an insertion sheath.

FIG. 10 is a view of the protection device of FIG. 8 in an expanded deployed profile in a vessel, shown with the insertion sheath withdrawn.

FIG. 12 is a detailed view of portion 120 of
5 the device shown in FIG. 11.

FIG. 14 is a view of the protection device of
10 FIG. 13 in an expanded deployed profile in a vessel.

FIG. 16 is a detailed view of portion 16 of
15 the device shown in FIG. 15.

FIG. 18 is a view of an alternate embodiment of a protection device in a collapsed profile, inserted into a vessel via an insertion sheath.

FIG. 20 is a view of the protection device of
25 FIG. 18 in a collapsed profile being withdrawn from the
vessel via a retrieval sheath.

FIG. 22 is a perspective view of an alternate
30 embodiment of a protection device, coupled to a
guidewire in an expanded deployed profile.

FIG. 23 is a view of the protection device of FIG. 22 in a collapsed profile in a vessel.

FIG. 24 is a view of the protection device of FIG. 22 in an expanded deployed profile in a vessel.

These drawings are for illustrative purposes only and are not necessarily drawn to scale.

5 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present invention relates to protection devices deployed in a body vessel or cavity for collection of loosened or floating debris such as embolic material dislodged during atherectomy or thrombectomy.

FIGS. 1-7 illustrate an embodiment of a protection device 20 or filter for collecting loosened debris in a body lumen. As illustrated comparatively in FIGS. 1-2, device 20 operates between a closed collapsed profile, adapted for insertion into a body lumen as illustrated in FIG. 2, and an open radially-expanded deployed profile for collecting debris in a body lumen as illustrated in FIG. 1.

Device 20 includes a filter 22 and a collapsible proximally-tapered frame 24. Frame 24 supports filter 22 and is operably coupled to an elongated guidewire 32 or other support device. Frame 24 includes a mouth 28 and a plurality of longitudinally-extending ribs 30. In an expanded profile, mouth 28 is opened and the ribs extend radially outwardly to support mouth 28. Preferably, a collar 33 movably couples the proximal ends of ribs 30 to guidewire 32. Mouth 28 is thus coupled to collar 33 through ribs 30 and is movable between a collapsed profile and an opened deployed profile, as will be explained.

Preferably, filter 22 is generally cone-shaped, having a proximal and a distal end. The distal end is a narrow, "V"-shaped end and is preferably

fixedly secured or formed to guidewire 32. The proximal end has a relatively wide opening and is coupled to mouth 28 of frame 24. Preferably, filter 22 is formed of a polymer membrane. In particular, filter 22 is preferably formed of a porous polyurethane material having a plurality of small openings 40. Filter 22 may be constructed of a polyurethane sheet, and openings 40 may be formed in the polyurethane sheet by known laser techniques. Holes or openings 40 are sized to allow blood flow therethrough but restrict flow of debris or emboli floating in the body lumen or cavity. In the embodiment shown, guidewire 32 extends through mouth 28 of device 20 and along the entire length of the device and is fixed to the distal end of filter 22.

Mouth 28 is generally formed of a pleated ring 34 having an expanded dimension to support filter 22 in the opened deployed profile as illustrated in FIGS. 1-3, and a collapsed dimension to support the filter in the closed collapsed profile as illustrated in FIG. 2. FIG. 3 is an end view of device 20 which illustrates pleated ring 34 in an open expanded profile. In the opened expanded profile, ring 34 includes a plurality of folds 36 which are spaced so that the diameter of the pleated ring 34 forms a mouth of sufficient diameter so that an opening to filter 22 conforms to a desired body lumen. Pleated ring 34 is collapsed by closing folds 36 as illustrated by arrows 38 so that adjacent folds 36 are positioned in close proximity. In such a position, the mouth assumes a relatively small dimension to collapse filter 22 for insertion and retrieval. As previously explained, pleated ring 34 is coupled to guidewire 32 via ribs 30 as shown in FIG. 3.

FIG. 4 illustrates a process of forming frame 24 and folds 36. Frame 24 may be formed from a wire

mesh sheet 42 having a series of rows of generally diamond-shaped structures 44. In one preferred embodiment, a portion 46 of a row is cut from wire mesh sheet 42 to form the frame 24. Portion 46 is rolled and sides 50, 52 are joined to form a continuous circular frame. A series of tips 54 on a first end are joined and coupled to ring 33 which slides over guidewire 26. A series of tips 56 on the second end form pleated ring 34 of mouth 28. In particular, tips 56 form the apex of folds 36, which expand and collapse as illustrated by arrows 38 in FIG. 3, to open and close mouth 28. Preferably, the wire mesh sheet 42 is formed of Nitinol or similar material having sufficient elasticity or resilience, as will be explained. The proximal end of filter 22 is then secured to mouth 28 via an adhesive or other suitable connection method. The distal end of filter 22 is then secured to guidewire 26 via adhesive or other techniques.

FIGS. 5-7 illustrate operation of protection device 20 which is inserted into a body lumen to collect floating debris or emboli. Briefly, as shown in FIG. 5, device 20 is inserted into a body lumen 60, such as a vascular lumen having a stenosis 62. Device 20 may be deployed distal of the blocked region or stenosis 62 to capture calcified material or substances dislodged during a medical procedure to open the stenosis 62. The stenosis 62 in a coronary vessel may be opened by known medical procedures such as dilatation or atherectomy.

More specifically, as shown in FIG. 5, device 20 is first collapsed and inserted in the collapsed profile into a delivery sheath 64. Sheath 64 is formed of a tubular member 66 including an inner lumen 68 extending therethrough. The profile of sheath 64 is relatively small to facilitate insertion and placement

10

20

30

through filter 22 to capture floating debris and particles.

After deployment, sheath 64 may be completely withdrawn and various treatment devices, such as an angioplasty dilatation catheter, stent delivery catheter or other atherectomy or thrombectomy devices, may be inserted for treatment. The treatment devices are inserted over guidewire 32 for placement relative to the treatment site. After treatment is complete, device 20 is removed as illustrated in FIG. 7.

As shown in FIG. 7, a retrieval sheath 72 is inserted as illustrated via arrow 74 for removal of device 20. Retrieval sheath 72 is formed of a tubular member 75 having a central lumen 76 and a distal opening sized to capture device 20. Retrieval sheath 72 is inserted to align the distal opening of sheath 72 with the proximal end of frame 24. Thereafter, sheath 72 is advanced; or, alternatively, in the embodiment shown, guidewire 32 is retracted, to collapse ribs 30, thereby collapsing mouth 28 and filter 22 as illustrated by arrows 78. In particular, ribs 30 (and the frame 24) are proximally sloped or tapered so that as sheath 72 is advanced over ribs 30, they collapse radially inwardly and collar 33 rides proximally on guidewire 32. As ribs 30 collapse inwardly, frame 24 folds at folds 36 until mouth 28 resides within retrieval sheath 72, or closely proximate the distal end of sheath 72, thereby trapping emboli therein. Device 20 and sheath 72 are then withdrawn from the vasculature.

Although longitudinally sloped ribs 30 are coupled to collar 33 in the device shown, ribs 30 may be directly fixed to guidewire 32 so that the filter is loosely supported in the collapsed profile. Alternatively, the device may be supported via an

alternate core wire or guidewire structure (not shown) which is coupled to frame 24 via ribs 30 but unlike guidewire 32 does not extend through the mouth and along the entire length of the filter so that device 20 does not have radial slack in the collapsed profile. Also, although device 20 is shown inserted distal of stenotic region 62 to capture material and debris dislodged during a treatment procedure, device 20 may be deployed in alternate positions for capturing floating debris or particles in other body cavities.

FIGS. 8-11 illustrate an alternate embodiment of a protection device 90. As illustrated in FIG. 8, protection device 90 includes a filter 92, a frame 94 and a collar 96. Protection device 90 is operably coupled to a guidewire 32 for operation as will be explained. Guidewire 32 is a typical guidewire having a small diameter for insertion into a tract to a treatment site, and preferably includes a spring coil tip.

Filter 92 includes a cone-shaped porous portion 100 and a pleated portion 102. Porous portion 100 includes a plurality of openings 104 to permit blood flow through filter 92 while restricting flow of debris or particles. A distal tip 106 of filter 92 is fixedly secured to guidewire 32. Preferably, filter portion 100 is formed of a polymer material, such as a polyurethane material, and holes or openings 104 are formed via known laser techniques.

Collar 96 is preferably formed of a relatively short tubular member having an inner lumen 108 and having notches 110 formed on an outer perimeter. Guidewire 32 extends through lumen 108 so collar 96 is slidably coupled to guidewire 32. Frame 94 is coupled to collar 96, and filter 92 is coupled to frame 94.

Preferably, frame 94 is formed of an elongated wire 112 having opposed ends. Opposed ends of wire 112 are coupled to collar 96 to form a mouth, and filter 92 (in particular, pleated portion 102) is coupled to wire 112 along substantially the entire length of wire 112. Preferably, guidewire 32 extends through collar 96 and through the mouth and extends along the entire longitudinal length of filter 92. Thus, collar 96 is moved proximally as illustrated by arrow 114 to collapse the mouth formed by frame 94 for insertion. Collar 96 is slid distally to expand the mouth formed by frame 94 and filter 92 to a deployment position.

Preferably, wire 112 is formed of a relatively elastic material such as Nitinol. Filter portion 102 is secured to wire loop 112 by one of various suitable attachment methods, including adhesives, stitching, or other known methods, to define the mouth of the device 90. Ends of wire 112 are also preferably coupled to collar 96 by known attachment methods, including adhesives.

Preferably, pleated filter portion 102 is formed of a polymer material such as polyurethane. The pleated filter portion 102 is preferably manufactured by winding a wire or other suitable coil around a polymer tube material. After the wire is wound around the tube, the tube is pressurized, causing the tube material to expand between the gaps in the wire, creating the pleats or creases which allow portion 102 to collapse. The coil is then removed, leaving collapsible portion 102. Construction of collapsible portion 102 is described in St. Germain, U.S. Patent No. 5,534,005, issued July 9, 1997, and assigned to Scimed Life Systems, Inc., hereby incorporated by reference.

The pleated filter portion 102 allows for the filter to expand or extend longitudinally to absorb impact pressure caused by embolic material received by filter portion 92 to maintain the placement of the device 90 during operation. Filter portion 100 and pleated portion 102 may be formed separately or from a single sheet of polymer material.

FIGS. 9-12 illustrate operation of device 90 in a patient's vasculature. Some parts are similar to those shown in FIGS. 5-7, and similar numbers are used to identify similar parts. As shown in FIG. 9, device 90 is inserted in a collapsed profile in cooperation with an insertion sheath 64 similar to that shown and described in FIG. 5. Tube 66 exerts a force on wire 112 and filter portions 100, 102 to collapse device 90. As illustrated, in the collapsed profile, collar 96 moves along wire 32 to longitudinally accommodate for radial slack of the collapsed device 90. Sheath 64 and device 90 are advanced to a deployment site, preferably distal of a stenotic region 62, for operation during a treatment procedure.

Once device 90 and sheath 64 are located at the deployment site, sheath 64 is withdrawn (while the position of guidewire 32 is maintained) as illustrated by arrow 116 so that the wire 112 expands radially outwardly (since the compression force is released). This causes filter 92 to expand to conform to the inner diameter of the vessel 60. As wire 112 expands outwardly, collar 96 slides distally along guidewire 32 for radial expansion of wire 112 and filter 92. Preferably, as previously explained, wire 112 is formed of a sufficiently elastic material to essentially spring outwardly after pressure is released, so that a tight interference between frame wire 112 and the vessel walls

of vessel 60 is maintained. This helps to ensure that the device 90 is sufficiently lodged against vessel wall 60 so that it stays in position during treatment and is not dislodged as a result of blood flow through the filter 92. In particular, sufficient pressure must be maintained so that the filter conforms to the diameter of vessel 60 and does not migrate due to force imparted to the filter when debris collects in the filter and so that no embolic material can slip between the filter and the walls of vessel 60.

Thereafter, treatment devices (not shown) may be advanced along guidewire 32 for placement relative to a stenosis 62 for treatment. Such treatment devices may include a dilatation catheter, stent delivery catheter or atherectomy or thrombectomy devices, etc. After treatment is completed, device 90 may be withdrawn as illustrated in FIGS. 11 and 12. Device 90 is withdrawn via a retrieval device 120. Retrieval device 120 is formed of a tubular member 122 having an inner lumen 124 and a locking tab 126 formed on an inner surface of the tubular member 122. Locking tab 126 mates with notch 110 formed on collar 96 for retrieval and removal of device 90.

Preferably, locking tab 126 is formed of a rigid extension having a sloped camming surface 130 and a flat locking surface 132. Notch 110 also includes a camming surface 134 and a flat locking surface 136. The camming surfaces 130, 134 are aligned so that, as sheath 120 is advanced, camming surfaces 130, 134 mate to slightly expand tube 122 so that locking member 126 on sheath 120 advances past notch 110 until the locking surfaces 132, 136 align and the camming force is released. This allows tube 122 to collapse to its original dimension with surfaces 132, 136 aligned to

lock device 90 to sheath 120 for withdrawing device 90. Sheath 120 is withdrawn proximally, as illustrated by arrow 140, while maintaining the position of guidewire 32. This causes collar 96 to slide proximally to
5 collapse device 90 along guidewire 32 thereby drawing wire 112 down over wire 32 and collapsing device 90. Once device 90 is collapsed, guidewire 32 and sheath 120 are collectively withdrawn to remove collapsed device 90.

10 FIGS. 13-16 illustrate an alternate embodiment of a protection device 150 where similar numbers are used to identify similar parts of previous embodiments. Device 150 is shown in operation in a vessel 60 having a stenosis 62. Device 150 includes a filter 152, a
15 frame 154, and a collar 156. Device 150 is operably coupled to guidewire 32 for operation. Filter 152 is preferably a cone-shaped member having proximal and distal ends 158, 160. The distal end 160 is generally "V"-shaped. Filter 152 may be formed from a polymer
20 sheet material similar to that described for previous embodiments and filter holes or openings 180 may be formed therein by laser techniques. Material and debris generally collect at the "V"-shaped tip to limit interference with blood flow through filter 152. The
25 "V"-shaped end 160 is fixedly coupled relative to guidewire 32. Proximal end 158 includes an opening which is supported relative to frame 154 to form a mouth of the device, as will be explained. Collar 156 is a tubular member 164 having an inner lumen 166 slidably
30 coupled relative to guidewire 32.

Frame 154 includes a generally circular mouth member 170 and a plurality of struts or ribs 172. Mouth 170 supports filter 152 and is preferably formed of a wire loop which is coupled thereto via a known adhesive

or other suitable means. The mouth is coupled to collar 156 via struts or ribs 172 so that the collar slides along guidewire 32 to selectively longitudinally extend device 150 to collapse device 150 for insertion and retrieval, and longitudinally shorten device 150 to expand device 150 (and mouth 170) for deployment. Preferably, struts 172 are attached to collar 156 and mouth 170 by any suitable means. Preferably, frame 154 (mouth 170 and struts or ribs 172) are formed of a wire or strip of a relatively elastic material such as a Nitinol material.

Device 150 includes compression spring 176 to bias device 150 in the longitudinally shortened (and thus radially expanded) profile having mouth 170 radially expanded for operation. In particular, spring 176 includes opposed ends, a first end is attached to collar 156, and a second end is attached to end 160 of filter 152. The compression spring 176 is normally biased to compress as illustrated by arrows 178 to bias the device in an opened deployed profile.

For insertion, device 150 is maintained in a low-profile position via sheath 64 as illustrated in FIG. 13 similar to that described for previous embodiments. In particular, sheath 64 exerts a force on frame 154 and filter 152 to compress frame 154 and filter 152 against the spring bias provided by compression spring 176. As shown in FIG. 13, insertion sheath 64 and device 150 are inserted into a patient and located distal of a stenosis 62 for deployment.

To deploy the device, the sheath 64 is withdrawn while the operator maintains the position of guidewire 32. Once sheath 64 is withdrawn from device 150, frame 154 and filter 152 expands radially outwardly under the force of the compression spring 176 to expand

mouth 170 to conform to the vessel walls 60 as illustrated in FIG. 14. Ribs 172 are extended outwardly to support mouth 170 in a radially-expanded position. The spring 176 maintains device 150 in a deployed position so that mouth 170 conforms to the opening of the vessel. Debris is captured and device 150 does not migrate under the load of the debris collected in filter 152.

After treatment is completed, device 150 may be withdrawn. Preferably, device 150 is withdrawn via a removal sheath 184, as illustrated in FIGS. 15-16. The removal sheath 184 includes an outer tubular extent 186 supporting an inner tube 188. The inner tube 188 includes a docking tip 190. Docking tip 190 includes docking latch 192 which cooperate with a latch 194 formed on an inner surface of collar 156. Docking latch 192 is formed of an arrow tip 190 defining sloped camming surface 196 and a lateral locking surface 198. Latch 194 on collar 156 includes a camming surface 200 and a lateral locking surface 202.

Sheath 184 is advanced over the guidewire 32 to insert tip 190 through the opening in tubular collar 156. Tip 190 is advanced until camming surfaces 196, 200 expand collar 156 to further advance arrow-shaped tip 190 until collar 156 collapses to align locking surfaces 198, 202 to lock device 150 to sheath 184 for withdrawal. After device 150 is locked to sheath 184, retrieval device 184 is first withdrawn proximally, as illustrated by arrow 204, while maintaining the position of guidewire 32 to force the frame 154 and filter 152 against the spring bias to a low-profile dimension. Thereafter, retrieval sheath 184 and guidewire 32 are collectively proximally withdrawn as illustrated to remove the device.

An alternate embodiment of a protective device is illustrated in FIGS. 17-20 and is formed independently of a guidewire 210. Guidewire 210 is formed of an elongated wire 212, preferably having a spring coil tip 214, and a protective device docking member 216 coupled to a distal portion of wire 212, as illustrated in FIG. 17. Docking member 216 is rigidly coupled to wire 212 and in one embodiment is formed of a generally "V"-shaped member 218 including a docking channel 220. Member 218 includes groove 222 which opens to channel 220. Docking member 216 is used to removably secure a protection device thereto as will be explained.

Docking member 216 may be permanently formed on the guidewire 210. Alternatively, docking member 216 may be detachably connected to guidewire 210 such as by a friction fit between guidewire 210 and a channel (not shown) of the docking member 216 or by a mechanical attachment mechanism. If a detachable, docking member 216 may be used on any suitable guidewire, thereby adapting the guidewire for operation with a protection device.

FIG. 18 illustrates an embodiment of a protection device 230 which may be selectively coupled to docking member 216. Protection device 230 includes a distal cone 232, a filter 152, a frame 154, and a collar 156. Cone 232 is coupled to a distal end of filter 152. Cone 232 is generally "V"-shaped and is formed of a rigid member having a distal opening (not shown) sized for insertion of guidewire 210 therethrough. Cone 232 includes a locking ring 242 extending about an outer perimeter of cone 232. Locking ring 242 is sized for insertion into groove 222 of docking member 216.

Thus, device 230 is mounted relative to the guidewire by inserting guidewire 210 through an opening in cone 232. Device 230 is advanced over guidewire 210 to align cone 232 with docking member 216. Cone 232 is forced into channel 220 of docking member 216 until ring 242 snaps into groove 222 and is maintained therein. Device 230 is inserted in a low-profile collapsed condition via cooperation with sheath 64, and is deployed by withdrawing sheath 64 while maintaining the position of guidewire 210 after device 230 is positioned at a treatment site (as comparatively illustrated in FIGS. 18-19) similar to that previously described with reference to FIGS. 13-14.

FIG. 20 illustrates withdrawal of device 230 via retrieval sheath 184, as previously described with reference to FIGS. 15-16. Sheath 184 is coupled to collar 156 and is then withdrawn proximally while maintaining the position of guidewire 210 to collapse device 230 to a low profile. Thereafter, sheath 184 and guidewire 210 are withdrawn to remove guidewire 210, protection device 230, and sheath 184 from the patient after treatment.

FIG. 21 illustrates an embodiment of a retrieval sheath 280 for operation with a distal protection device 282 for collapsing the distal protection device for withdrawal. The retrieval sheath 280 includes a telescoping tubular structure including an outer tubular member 283 and an inner tubular member 284. Outer tubular member 283 includes a lumen 286, and inner tubular member 284 extends through lumen 286 and is movable therein to form the telescoping tubular structure.

Outer tubular member 283 is formed of a composite structure including a first tubular portion

288 and a second tubular portion 290. The first tubular portion 288 includes a proximal end (not shown) and a distal end 292. The second tubular portion 290 includes a proximal end 294 and a distal end 296. Proximal end 294 is coupled to distal end 292 of tubular member 288 to form a composite outer tubular structure 283 having a proximal end (not shown) and distal end 296.

Inner tube 284 includes a proximal end (not shown) and a distal end 298. Inner tube 284 includes a first diameter portion 300, a second diameter portion 304, a transition portion 306, and tapered flanged end 308. First and second portions 300, 304 are coupled via transition portion 306. Flanged end 308 has a relatively large tapered mouth for capturing and progressively collapsing a deployed protection device as will be explained.

The proximal end of inner tube 284 extends through outer tube 283 and exits from proximal end of outer tube 283 for providing a mechanism for slidably moving inner tube 284 within outer tube 283. Flanged end 308 is relatively flexible and resilient and is biased in a radially expanded position so that it opens to an expanded tapered profile, as illustrated in FIG. 21, when flanged end 308 extends beyond distal end 296 of outer tube 283. When flanged end 308 is retracted within inner tube 283 as illustrated via arrow 310, flanged end 308 collapses as illustrated by arrows 312 to assume the dimension of outer tube 283 in a collapsed position (not shown). Flanged end 308 may be formed of a pleated material or simply a relatively elastic material.

In operation, retrieval sheath 280 is inserted into a patient's vasculature with flanged end 308 in a collapsed position within inner tube 283 to provide a

low profile for insertion. Retrieval sheath 280 is inserted and aligned closely proximate to deployed protection device 282. Once retrieval device 280 is aligned, inner tube 284 is slid distally relative to
5 outer tube 282 to expand flanged end 308 to an expanded profile, as illustrated in FIG. 21, to surround the deployed protection device. Thereafter, sheath 280 may be advanced, or protection device 282 may be withdrawn proximally via guidewire 32 to forcibly collapse
10 protection device 282 as protection device 282 is withdrawn along the tapered inner channel of flanged end 308. Retrieval device 280, protection device 282, and guidewire 32 are then withdrawn. The device thus provides a system for capturing a protection device 282
15 and filtered contents (debris, emboli, etc.) along therewith to minimize post-procedural embolic events. Preferably, inner and outer tubes 282, 284 are formed of a polymer material, and flanged end 308 is formed of a polymer membrane. Although a particular embodiment of
20 retrieval device 280 is shown, it should be understood that construction of device 280 is not limited to the exact construction shown.

FIGS. 22-24 illustrate an alternate embodiment of a distal protection device 320. As shown in FIG. 23,
25 distal protection device 320 is coupled to a guidewire 322 to operate between a radially-expanded deployed profile illustrated in FIGS. 22 and 24, and a collapsed profile illustrated in FIG. 23 for insertion and retrieval. Guidewire 322 is formed of a tubular member
30 324 including a central lumen 326 therethrough. The guidewire 322 may be formed of a hypo tube or other material. The distal protection device 320 includes a filter 328 and a frame 330.

Preferably, frame 330 is formed of an elongate wire 332 and a polymer sleeve 334. Frame 330 is coupled to guidewire 322 and is supported thereby between the insertion dimension illustrated in FIG. 23 and the deployed dimension illustrated in FIGS. 22 and 24. Filter 328 is coupled to frame 330 and is supported thereby at its proximal end by frame 330. Filter 328 may be formed of a polymer sheet material or a mesh-like material having holes or openings 336 therein to allow blood to flow therethrough while restricting flow of emboli, debris and clotting material. Filter 328 is cone-shaped, preferably having a "V"-shaped tip and a large opening to funnel debris for collection. Filter 328 and sleeve 334 may be integrally or separately formed, and secured via known attachment methods such as known adhesives.

Guidewire 322 includes spaced distal openings 338, 340 which communicates with inner lumen 326. Opposed ends of sleeve 334 are coupled to spaced openings 338, 340 so the lumen through sleeve 334 forms a path for frame wire 332. Frame wire 332 extends from a proximal end (not shown) of the guidewire 322 through lumen 326, through openings 338 and 340, and is anchored at a distal end of lumen 326 (preferably proximate to opening 340). Frame wire 332 also extends through sleeve 334 to form an external loop 342 defining the mouth of the protection device 320. External loop 342 is tightened by pulling the wire 332 proximally, and is opened by pushing the wire 332 distally, as illustrated by arrow 344, to open and close the mouth of protection device 320.

FIGS. 23-24 illustrate operation of protection device 320. As illustrated in FIG. 23, the device is inserted in a low-profile dimension by proximally

retracting wire 332 to close external loop 342 to locate device 320 at a deployment site, preferably distal of a stenosis 62. Frame wire 332 is moved distally as illustrated by arrow 344 to expand loop 342 to open the mouth to filter 328 to conform to the dimension of vascular lumen 60, as illustrated in FIG. 24. As the mouth of the device 320 is expanded to conform to the vascular dimension, guidewire 322 pushes against a lumen wall to provide a tight fit between filter 328 and vascular wall 60.

The mouth has a dimension which conforms to the vascular wall, and cone-shaped filter 328 funnels material to a tip of the filter to allow bloodflow to continue therethrough. Device 320 is collapsed after use for removal. To collapse the device for withdrawal, frame wire 332 is moved proximally, as illustrated by arrow 346 in FIG. 24, to collapse or close external loop 342 to the low-profile collapsed dimension illustrated in FIG. 23.

In the embodiment illustrated in FIGS. 23-24, a pressure-sensing device 350 may be inserted through lumen 326 of guidewire 322. The pressure-sensing device 350 is formed of an elongated member 352 having a distal tip 354 which is curve-shaped to align a pressure sensor facing the direction of blood flow or fluid flow through vessel 60. Proximal circuitry is coupled to the pressure sensor at distal tip 354 to provide a pressure reading to an operator. Of course, device 350 may simply be a hollow tube with the pressure sensing mechanism located entirely at a proximal end of device 350. The pressure reading indicates whether the blood vessel or vascular vessel 60 is occluded distal of protection device 320, to ensure proper blood flow through protection device 320. Thus, if emboli,

5

10

15

WHAT IS CLAIMED IS:

1. A device adapted for deployment in a body vessel, comprising:
 - a filter having a plurality of openings for fluid flow therethrough; and
 - a proximally-tapered collapsible frame coupled to the filter and operably coupled to a guidewire, said frame including an expandable mouth coupled to the filter and adapted to operate between an expanded profile and a collapsed profile, and longitudinal ribs having opposed first and second ends, said first ends being coupled to the guidewire, and said second ends being coupled to the mouth, said ribs being sloped outwardly in an expanded position to form the proximally tapered collapsible frame.
2. The device of claim 1 wherein the mouth is normally biased in the expanded profile.
3. The device of claim 2 wherein the mouth is formed of a resilient wire material.
4. The device of claim 1 wherein the mouth and ribs are integrally formed from a mesh sheet material.
5. The device of claim 1 wherein the filter has a distal end fixedly coupled to the guidewire.
6. The device of claim 1 wherein the filter is generally cone-shaped.

7. The device of claim 1 wherein mouth is formed of a pleated ring.
8. The device of claim 1 wherein ribs are fixedly secured to the guidewire.
9. The device of claim 1 and further comprising a collar slidably disposed over the guidewire and wherein the ribs are coupled to the collar, the guidewire extending through the mouth and along a length of the filter.
10. The device of claim 1 wherein the frame includes at least four ribs.
11. The device of claim 7 wherein the pleated ring includes at least four folds.
12. The device of claim 1 wherein the mouth and ribs are integrally formed.
13. In combination:
 - a device adapted for deployment in a body vessel including:
 - a filter having a plurality of openings for fluid flow therethrough, said filter being adapted to be coupled to a wire for operation;
 - a proximally-tapered collapsible frame coupled to the filter and operably coupled to the core wire, said frame including an expandable mouth adapted to operate between an expanded profile and a collapsed

a sheath formed of a tubular member sized for placement over the ribs to collapse the mouth and filter to the collapsed profile.

- providing a device coupled to a guidewire and movable relative thereto, having a filter and a frame for supporting the filter in a collapsed profile and an expanded deployed profile, said frame being normally biased in the expanded deployed profile;

positioning the device in the lumen of the sheath to maintain the device in a collapsed profile;

inserting the sheath and device into a body lumen and advancing the distal end of the sheath to locate the device at a deployment site; and

[illegible]

-
- The figure consists of seven vertically stacked histograms labeled \$k=0\$ at the bottom to \$k=7\$ at the top. Each histogram shows the frequency of the number of non-zero elements in the vector \$\mathbf{x}_k\$. The x-axis for all plots ranges from 0 to 100. The y-axis represents frequency, with scales varying between plots: \$k=0\$ has a scale up to 8; \$k=1\$ up to 10; \$k=2\$ up to 12; \$k=3\$ up to 14; \$k=4\$ up to 16; \$k=5\$ up to 18; and \$k=6\$ up to 20. As \$k\$ increases, the peak of the distribution shifts to the right, indicating that vectors with more non-zero elements become more frequent.

-

ABSTRACT OF THE DISCLOSURE

A device adapted for deployment in a body vessel for collecting floating debris and emboli in a filter. The device includes a collapsible proximally tapered frame for operably supporting the filter between a collapsed insertion profile and an expanded deployment profile. The tapered collapsible frame includes a mouth which is sized to extend to walls of the body vessel in the expanded deployed profile to seal the filter relative to the body vessel for collecting debris floating in the body vessel.

COMBINED DECLARATION AND
POWER OF ATTORNEY
IN ORIGINAL APPLICATION

Attorney Docket No.

S13.12-0030

SPECIFICATION AND INVENTORSHIP IDENTIFICATION

As a below named inventor, I declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and joint inventor of the subject matter which is claimed, and for which a patent is sought, on the invention entitled DISTAL PROTECTION DEVICE AND METHOD the specification of which,

(check one) ☐ is attached hereto.

☒ was filed on March 5, 1998 as Appln. Serial No. 09/035,740.

☐ and was amended on .

☐ was described and claimed in PCT International Application No. filed on and as amended under PCT Article 19 on .

ACKNOWLEDGEMENT OF REVIEW OF PAPERS AND DUTY OF CANDOR

I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above. I acknowledge the duty to disclose information which is known to me to be material to the patentability of this application in accordance with Title 37, Code of Federal Regulations, § 1.56.

PRIORITY CLAIM (35 USC § 119)

I claim foreign priority benefits under Title 35, United States Code, § 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s)

Number	Country	Day/Month/Year Filed	Priority Claimed
_____	_____	_____	Yes_____ No_____
_____	_____	_____	Yes_____ No_____

PRIORITY CLAIM (35 USC § 120)

I claim the benefit under Title 35, United States Code, § 120 of any United States application(s) listed below. Insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35 United States Code § 112, I acknowledge the duty to disclose to the Patent Office all information known to me to be material to patentability as defined in Title 37 Code of Federal Regulations § 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application:

Appln. Ser. No.	U.S. Serial No. (if any under PCT)	Filing Date	Status
<u>08/943,358</u>	<u></u>	<u>October 3, 1997</u>	<u>Pending</u>
<u>08/810,825</u>	<u></u>	<u>March 6, 1997</u>	<u>Pending</u>

DECLARATION

I declare that all statements made herein that are of my own knowledge are true and that all statements that are made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

POWER OF ATTORNEY

I appoint the following attorneys and agents to prosecute the patent application identified above and to transact all business in the Patent and Trademark Office connected therewith, including full power of association, substitution and revocation: Judson K. Champlin, Reg. No. 34,797; Joseph R. Kelly, Reg. No. 34,847; Nickolas E. Westman, Reg. No. 20,147; Steven M. Koehler, Reg. No. 36,188; David D. Brush, Reg. No. 34,557; John D. Veldhuis-Kroeze, Reg. No. 38,354; Deirdre Megley Kvale, Reg. No. 35,612; Theodore M. Magee, Reg. No. 39,758; Robert E. Atkinson, Reg. No. 36,433; Luke R. Dohmen, Reg. No. 36,783; Peter J. Gafner, Reg. No. 36,517; and John A. Rissman, Reg. No. 33,764.

I ratify all prior actions taken by Westman, Champlin & Kelly, P.A. or the attorneys and agents mentioned above in connection with the prosecution of the above-mentioned patent application.

DESIGNATION OF CORRESPONDENCE ADDRESS

Please address all correspondence and telephone calls to Joseph R. Kelly in care of:

WESTMAN, CHAMPLIN & KELLY, P.A.
Suite 1600 - International Centre
900 Second Avenue South
Minneapolis, Minnesota 55402-3319
Phone: (612) 334-3222 Fax: (612) 334-3312

Inventor: *[Signature]*
(Signature)

Date: 1/6/78

Inventor: Thomas E. Broome
(Printed Name)

Residence: Hopkins, Minnesota Citizenship: U.S.A.

P.O. Address: 511 Sunnyside Lane, Hopkins, Minnesota 55343

Inventor: John M.K. Daniel
(Printed Name)



Residence: PLYMOUTH, Hopkins, Minnesota Citizenship: U.S.A. INDIA *JA*
P.O. Address: 12705 48th AVE NORTH, PLYMOUTH,
701 Oak Park Lane, #61, Hopkins, Minnesota 55342 55442 *7/9/98*

Inventor: Thos. P. Holt Date: 8 July 98
(Signature)

Inventor: Thomas R. Hektner
(Printed Name)

Residence: Medina, Minnesota Citizenship: U.S.A.

P.O. Address: 825 Navajo Road, Medina, Minnesota 55340








Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11










Fig. 12







9/12






Fig. 19






Fig. 20






Fig. 23




Fig. 24

P A T E N T

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of: Broome et al.

Serial No.: 09/035,740

Examiner: Smith, J.

Filed: March 5, 1998

Group Art Unit: 3732


For: DISTAL PROTECTION DEVICE AND METHOD

Docket No.: 1001.1350101

REVOCATION OF PRIOR POWERS OF ATTORNEY
AND POWER OF ATTORNEY

Assistant Commissioner
for Patents
Washington, D.C. 20231

I HEREBY CERTIFY THAT THIS CORRESPONDENCE IS
BEING DEPOSITED WITH THE UNITED STATES
POSTAL SERVICE AS FIRST CLASS MAIL IN AN
ENVELOPE ADDRESSED TO ASSISTANT
COMMISSIONER FOR PATENTS, WASHINGTON, D.C.
20231.

2nd DAY OF August 1999


Dear Sir:

SciMed Life Systems, Inc., the owner of the entire right, title and interest in and to the above-identified patent/application, hereby revokes all previous powers of attorney and appoints the following attorneys and/or agents to prosecute the above-identified patent or application, including all continuations and divisionals thereof, and to transact all business in the U.S. Patent and Trademark Office connected therewith: David M. Crompton, Reg. No. 36,772; Glenn M. Seager, Reg. No. 36,926; Brian N. Tufte, Reg. No. 38,638; Craig F. Taylor, Reg. No. 40,199; Robert E. Atkinson, Reg. No. 36,433; Allen W. Groenke, Reg. No. 42,608; Luke Dohmen, Reg. No. 36,783; Peter J. Gafner, Reg. No. 36,517; Robert M. Rauker, Reg. No. 40,782; Todd P. Messal, Reg. No. 42,883; David L. Cavanaugh, Reg. No. 36,476; Patricia LaMarche-Davis, Reg. No. 37,866; Mark J. Casey, Reg. No. 37,796; and William J. Shaw, Reg. No. 43,111.

Pursuant to 37 C.F.R. § 3.73(b), SciMed Life Systems, Inc., a corporation, certifies that it is the assignee of the entire right, title and interest in the patent application identified above by virtue of an assignment, recorded on August 13, 1998, at Reel 9387, Frame 0230.

The undersigned (whose title is supplied below) is empowered to act on behalf of the assignee by virtue of the attached Limited Authorization to Act on Behalf of Assignee Regarding Certain Patent Matters.

Address all telephone calls to Glenn M. Seager at telephone number (612) 677-9050.

Address all correspondence to Glenn M. Seager, CROMPTON, SEAGER & TUFTE, LLC, 331 Second Avenue South, Suite 895, Minneapolis, Minnesota 55401-2246.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that willful false statements may jeopardize the validity of the application or any patent issued thereon.

Respectfully submitted,

SCIMED LIFE SYSTEMS, INC.

Date: 7/22/99

By: Robert M. Ranker